

5300 Beethoven Street, Los Angeles, CA 90066 TEL: (310)306-5556 • FAX: (310)821-7413 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

Electrical

24

MODEL 5048

150 kHz - 230 MHz 75 WATTS LINEAR POWER RF AMPLIFIER

Specification @ 25° C

0.15 - 230 MHz

Solid State Broadband High Power RF Amplifier

The 5048 is a 75 Watt broadband amplifier that covers the 0.15 – 230 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 5048 comes with an extended multiyear warranty.

	2	Saturated Output Power	75 Watts typical
	3	Power Output @ 1dB Comp.	45 Watts min
	4	Small Signal Gain	+49 dB min
	5	Small Signal Gain Flatness	<u>+</u> 1.5 dB max
	6	IP ₃	+52 dBm typical
	7	Input VSWR	2:1 max
	8	Harmonics	-15 dBc typical @ 45 Watts
	9	Spurious Signals	> -60 dBc typical @ 45 Watts
	10	Input/Output Impedance	50 Ohms nominal
	11	AC Input Power	400 Watts max
	12	AC Input	100 – 240 VAC, single phase
	13	RF Input	0 dBm
	14	RF Input Signal Format	CW/AM/FM/PM/Pulse
	15	Class of Operation	AB
	<u>Mechanical</u>		
	16	Dimensions	19" x 5.25" x 20"
	17	Weight	48 lb. max
	18	Connectors	Type-N
	19	Grounding	Chassis
	20	Cooling	Internal Forced Air
<u>Environmental</u>			
	21	Operating Temperature	0° C to +50° C
	22	Operating Humidity	95% Non-condensing
	23	Operating Altitude	Up to 10,000' Above Sea Level

<u>Parameter</u>

Frequency Range

Specifications subject to change without notice

Normal Truck Transport

CIRCUIT PROTECTIONS

- ♦ Thermal Overload
- ♦ Over Current
- ♦ Over Voltage

ORDERING MODELS

- ♦ R Rear Panel Connectors
- ◊ F Front Panel Connectors
- ♦ RE R model w/Control Option
- ♦ FE F model w/Control Option
- ♦ RT RE model w/Ethernet Interface
- ♦ FT FE model w/Ethernet Interface



Shock and Vibration

F Model Shown

Approved By:	D-4
Annroved By:	Date:
ADDIOVED DV.	Date.