

5300 Beethoven Street, Los Angeles, CA 90066 TEL: (310)306-5556 • FAX: (310)821-7413
WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 5124

20 - 1000 MHz 20 WATTS LINEAR POWER RF AMPLIFIER

Solid State Broadband High Power RF Amplifier

The 5124 is a 20 Watt broadband amplifier that covers the 20 – 1000 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 5124 comes with an extended multiyear warranty.

CIRCUIT PROTECTIONS

- Or Thermal Overload
- ◊ Over Current
- Over Voltage

ORDERING MODELS

- R Rear Panel Connectors
- ◊ F Front Panel Connectors
- RE R model w/Control Option
- ◊ FE F model w/Control Option
- ◊ RT RE model w/Ethernet Interface
- ♦ FT FE model w/Ethernet Interface

Approved By:

	-	
	Parameter	Specification @ 25° C
Electrical		
1	Frequency Range	20 – 1000 MHz
2	Saturated Output Power	20 Watts typical
3	Power Output @ 1dB Comp.	13 Watts min
4	Small Signal Gain	+44 dB min
5	Small Signal Gain Flatness	<u>+</u> 1.5 dB max
6	IP ₃	+47 dBm typical
7	Input VSWR	2:1 max
8	Harmonics	-20 dBc typical @ 13 Watts
9	Spurious Signals	> -60 dBc typical @ 13 Watts
10	Input/Output Impedance	50 Ohms nominal
11	AC Input Power	160 Watts max
12	AC Input	100 – 240 VAC, single phase
13	RF Input	0 dBm max
14	RF Input Signal Format	CW/AM/FM/PM/Pulse
15	Class of Operation	AB
Mechanical		
16	Dimensions	19" x 3.5" x 18"
17	Weight	28 lb. max
18	Connectors	Type-N
19	Grounding	Chassis
20	Cooling	Internal Forced Air
Environmental		
21	Operating Temperature	0° C to +50° C
22	Operating Humidity	95% Non-condensing
23	Operating Altitude	Up to 10,000' Above Sea Level
24	Shock and Vibration	Normal Truck Transport

Specifications subject to change without notice.

