

5300 Beethoven Street, Los Angeles, CA 90066 TEL: (310)306-5556 • FAX: (310)821-7413 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

## **MODEL 4014**

800 - 1000 MHz **100 WATTS** LINEAR POWER RF AMPLIFIER

## Solid State **Band-specific High Power RF Amplifier**

The 4014 is a 100 Watt band-specific amplifier that covers the 800 - 1000 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3<sup>rd</sup> order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR<sub>RF</sub> amplifiers, the 4014 comes with an extended multiyear warranty.

	<u>Parameter</u>	Specification @ 25° C
<u>Electrical</u>		
1	Frequency Range	800 – 1000 MHz
2	Saturated Output Power	100 Watts typical
3	Power Output @ 1dB Comp.	60 Watts min
4	Small Signal Gain	+51 dB min
5	Small Signal Gain Flatness	<u>+</u> 1.5 dB max
6	IP <sub>3</sub>	+54 dBm typical
7	Input VSWR	2:1 max
8	Harmonics	-20 dBc typical @ 60 Watts
9	Spurious Signals	> -60 dBc typical @ 60 Watts
10	Input/Output Impedance	50 Ohms nominal
11	AC Input Power	400 Watts max
12	AC Input	100 – 240 VAC, single phase
13	RF Input	0 dBm max
14	RF Input Signal Format	CW/AM/FM/PM/Pulse
15	Class of Operation	AB
<u>Mechanical</u>		
16	Dimensions	19" x 5.25" x 18"
17	Weight	48 lb. max
18	Connectors	Type-N
19	Grounding	Chassis
20	Cooling	Internal Forced Air
<u>Environmental</u>		
21	Operating Temperature	0° C to +50° C
22	Operating Humidity	95% Non-condensing
23	Operating Altitude	Up to 10,000' Above Sea Level
24	Shock and Vibration	Normal Truck Transport  Specifications subject to change without notice.

## **CIRCUIT PROTECTIONS**

- ♦ Thermal Overload
- ♦ Over Current
- ◊ Over Voltage
- ♦ Infinite Load VSWR Protection

## 0

- $\Diamond$
- $\Diamond$
- $\Diamond$
- $\Diamond$
- $\Diamond$
- $\Diamond$

ORDERING MODELS	MALE POWER AND THE	
♦ R - Rear Panel Connectors	The The Table To Marin	
◊ F - Front Panel Connectors		
♦ RE - R model w/Control Option		
♦ FE - F model w/Control Option		
♦ RT - RE model w/Ethernet Interface	F Model Shown	
♦ FT - FE model w/Ethernet Interface	F Woder Shown	
Approved By:	Date:	