

5300 Beethoven Street, Los Angeles, CA 90066 TEL: (310)306-5556 • FAX: (310)821-7413 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 5077

500 - 1000 MHz 50 WATTS LINEAR POWER RF AMPLIFIER

Solid State Broadband High Power RF Amplifier

The 5077 is a 50 Watt broadband amplifier that covers the 500 – 1000 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 5077 comes with an extended multiyear warranty.

CIRCUIT PROTECTIONS

- ♦ Thermal Overload
- ♦ Over Current
- ◊ Over Voltage

			114.1			DEI	
•		166		12	N/I ()		•
\mathbf{u}	\mathbf{n}	μ	114	u		$\boldsymbol{\nu}$	

- ♦ R Rear Panel Connectors
- ◊ F Front Panel Connectors
- ♦ RE R model w/Control Option
- ♦ FE F model w/Control Option
- ♦ RT RE model w/Ethernet Interface
- ♦ FT FE model w/Ethernet Interface

	<u>Parameter</u>	Specification @ 25° C			
<u>Electrical</u>					
1	Frequency Range	500 – 1000 MHz			
2	Saturated Output Power	50 Watts typical			
3	Power Output @ 1dB Comp.	30 Watts min			
4	Small Signal Gain	+48 dB min			
5	Small Signal Gain Flatness	<u>+</u> 1.5 dB max			
6	IP ₃	+51 dBm typical			
7	Input VSWR	2:1 max			
8	Harmonics	-20 dBc typical @ 30 Watts			
9	Spurious Signals	> -60 dBc typical @ 30 Watts			
10	Input/Output Impedance	50 Ohms nominal			
11	AC Input Power	200 Watts max			
12	AC Input	100 – 240 VAC, single phase			
13	RF Input	0 dBm			
14	RF Input Signal Format	CW/AM/FM/PM/Pulse			
15	Class of Operation	AB			
<u>Mechanical</u>					
16	Dimensions	19" x 3.5" x 18"			
17	Weight	30 lb. max			
18	Connectors	Type-N			
19	Grounding	Chassis			
20	Cooling	Internal Forced Air			
<u>Environmental</u>					
21	Operating Temperature	0° C to +50° C			
22	Operating Humidity	95% Non-condensing			
23	Operating Altitude	Up to 10,000' Above Sea Level			
24	Shock and Vibration	Normal Truck Transport			

Specifications subject to change without notice



RE Model Shown

Approved By:	Date:	